

2G - Natural Gas - 35% - 40°C - NOx 500

Technical data

800 kWel; 480 V, 60 Hz; Natural gas, MN = 80

Design conditions

Comb. air temperature / rel. Humidity:	[°C] / [%]	25 / 60
Altitude:	[m]	100
Exhaust temp. after heat exchanger:	[°C]	120
NO _x Emission (tolerance - 8%):	[mg/Nm ³ @5%O ₂]	500

Fuel gas data: 2)

Methane number:	[-]	80
Lower calorific value:	[kWh/Nm ³]	10,17
Gas density:	[kg/Nm ³]	0,79
Standard gas:	Natural gas, MN = 80	

Genset:

Engine:	TCG 2016 V16 C	
Speed:	[1/min]	1800
Configuration / number of cylinders:	[-]	V / 16
Bore / Stroke / Displacement:	[mm]/[mm]/[dm ³]	132 / 160 / 35
Compression ratio:	[-]	12,0
Mean piston speed:	[m/s]	9,6
Mean lube oil consumption at full load:	[g/kWh]	0,2
Engine-management-system:	[-]	TEM EVO

Generator:	Marelli MJB 400 LC4	
Voltage / voltage range / cos Phi:	[V] / [%] / [-]	480 / ±10 / 1
Speed / frequency:	[1/min] / [Hz]	1800 / 60

Energy balance

Load:	[%]	100	75	50
Electrical power COP acc. ISO 8528-1:	[kW]	800	600	400
Engine jacket water heat:	[kW ±8%]	386	311	247
Intercooler LT heat:	[kW ±8%]	58	35	21
Lube oil heat:	[kW ±8%]			
Exhaust heat with temp. after heat exchanger:	[kW ±8%]	506	413	305
Exhaust temperature:	[°C ±25°C]	490	510	530
Exhaust mass flow, wet:	[kg/h]	4444	3431	2403
Combustion mass air flow:	[kg/h]	4294	3314	2319
Radiation heat engine / generator:	[kW ±8%]	30 / 26	23 / 21	15 / 18
Fuel consumption:	[kW+5%]	1929	1498	1073
Electrical / thermal efficiency:	[%]	41,5 / 46,3	40,0 / 48,3	37,3 / 51,4
Total efficiency:	[%]	87,8	88,3	88,7

System parameters 1)

Ventilation air flow (comb. air incl.) with ΔT = 15K	[kg/h]	22100
Combustion air temperature minimum / design:	[°C]	20 / 25
Exhaust back pressure from / to:	[mbar]	30 / 50
Maximum pressure loss in front of air cleaner:	[mbar]	5
Zero-pressure gas control unit selectable from / to: 2)	[mbar]	20 / 200
Pre-pressure gas control unit selectable from / to: 2)	[bar]	0,5 / 10
Starter battery 24V, capacity required:	[Ah]	286
Starter motor:	[kWel.] / [VDC]	9 / 24
Lube oil volume engine / external oil tank:	[dm ³]	135 / 260
Dry weight engine / genset:	[kg]	3090 / 7000

Cooling system

Glycol content engine jacket water / intercooler:	[% Vol.]	0 / 35
Water volume engine jacket / intercooler:	[dm ³]	56 / 5
KVS / Cv value engine jacket water / intercooler:	[m ³ /h]	43 / 10
Jacket water coolant temperature in / out:	[°C]	84 / 92
Intercooler coolant temperature in / out:	[°C]	40 / 46
Engine jacket water flow rate from / to:	[m ³ /h]	39 / 60
Water flow rate engine jacket water / intercooler:	[m ³ /h]	43 / 10
Water pressure loss engine jacket water / intercooler:	[bar]	1,0 / 1,0

1) See also "Layout of power plants":

2) See also Techn. Circular 0199-99-3017

Frequency band f [Hz]	25	31,5	40	50	63	80	100	125	160	200	250	315	400	500	630	800	1k	1.25k	1.6k	2k	2.5k	3.15k	4k	5k	6.3k	8k	10k	12.5k	16k	L _{WA} [dB(A)]	S [m ²]
Air-borne noise 3)	86,1	90,5	92,3	97,3	103,4	104,3	107	111,4	106,4	109	107,1	111	113,7	108,9	106,7	106,8	106,6	108,7	105,9	105,2	105,6	103,5	104	104,8	121,4	112,8	97,9	99	92,8	123,2	83
Exhaust noise 4)				120			135			130			124			122			116			117			109					128	15,2

3) DIN EN ISO 3746 (σ_{RD}=±4 dB)

4) DIN 45635-11 Appendix A (±3 dB)

L_W: Sound power level

S: Area of measurement surface (S₀=1m²)