

2G - Natural Gas - 35% - 40°C - NOx 500

Technical data

1560 kWel; 480 V, 60 Hz; Natural gas, MN = 80

Design conditions

Comb. air temperature / rel. Humidity:	[°C] / [%]	25 / 60
Altitude:	[m]	100
Exhaust temp. after heat exchanger:	[°C]	120
NO _x Emission (tolerance - 8%):	[mg/Nm ³ @5%O ₂]	500

Fuel gas data: 2)

Methane number:	[-]	80
Lower calorific value:	[kWh/Nm ³]	10,17
Gas density:	[kg/Nm ³]	0,79
Standard gas:	Natural gas, MN = 80	

Genset:

Engine:	TCG2020V16	
Speed:	[1/min]	1500
Configuration / number of cylinders:	[-]	V / 16
Bore / Stroke / Displacement:	[mm]/[mm]/[dm ³]	170 / 195 / 71
Compression ratio:	[-]	13,0
Mean piston speed:	[m/s]	9,8
Mean lube oil consumption at full load:	[g/kWh]	0,2
Engine-management-system:	[-]	TEM EVO

Generator:	Marelli MJB 500 MC4	
Voltage / voltage range / cos Phi:	[V] / [%] / [-]	480 / ±5 / 1
Speed / frequency:	[1/min] / [Hz]	1800 / 60

Gear box:	Eisenbeiss GU 320	
Lube oil volume of gear box:	[dm ³]	58

Energy balance

Load:	[%]	100	75	50
Electrical power COP acc. ISO 8528-1:	[kW]	1560	1170	780
Engine jacket water heat:	[kW ±8%]	804	615	445
Intercooler LT heat:	[kW ±8%]	144	102	60
Lube oil heat:	[kW ±8%]			
Exhaust heat with temp. after heat exchanger:	[kW ±8%]	785	645	489
Exhaust temperature:	[°C ±25°C]	420	443	474
Exhaust mass flow, wet:	[kg/h]	8589	6522	4500
Combustion mass air flow:	[kg/h]	8306	6303	4346
Radiation heat engine / generator:	[kW ±8%]	54 / 49	53 / 42	42 / 37
Fuel consumption:	[kW+5%]	3631	2806	1977
Electrical / thermal efficiency:	[%]	43,0 / 43,8	41,7 / 44,9	39,4 / 47,3
Total efficiency:	[%]	86,8	86,6	86,7

System parameters 1)

Ventilation air flow (comb. air incl.) with ΔT = 15K	[kg/h]	40800
Combustion air temperature minimum / design:	[°C]	20 / 25
Exhaust back pressure from / to:	[mbar]	30 / 50
Maximum pressure loss in front of air cleaner:	[mbar]	5
Zero-pressure gas control unit selectable from / to: 2)	[mbar]	20 / 200
Pre-pressure gas control unit selectable from / to: 2)	[bar]	0,5 / 10
Starter battery 24V, capacity required:	[Ah]	430
Starter motor:	[kWel.] / [VDC]	15 / 24,0
Lube oil content engine / base frame:	[dm ³]	265 / 685
Dry weight engine / genset:	[kg]	6090 / 14900

Cooling system 5)

Glycol content engine jacket water / intercooler:	[% Vol.]	0 / 35
Water volume engine jacket / intercooler:	[dm ³]	151 / 20
KVS / Cv value engine jacket water / intercooler:	[m ³ /h]	46 / 30
Jacket water coolant temperature in / out:	[°C]	80 / 93
Intercooler coolant temperature in / out:	[°C]	40 / 44
Engine jacket water flow rate from / to:	[m ³ /h]	50 / 65
Water flow rate engine jacket water / intercooler:	[m ³ /h]	55 / 35
Water pressure loss engine jacket water / intercooler:	[bar]	1,4 / 1,4

1) See also "Layout of power plants":

2) See also Techn. Circular 0199-99-3017

5) Gear oil cooling within intercooler coolant circuit

Frequency band f [Hz]	25	31,5	40	50	63	80	100	125	160	200	250	315	400	500	630	800	1k	1.25k	1.6k	2k	2.5k	3.15k	4k	5k	6.3k	8k	10k	12.5k	16k	L _{WA} [dB(A)]	S [m ²]																									
Air-borne noise 3)	99,1	96,8	100,2	102,5	104,3	109,6	116,6	113,4	118,1	117,2	116,9	113,2	112,5	112,7	113,7	112,8	113,2	114,7	113	113,8	113	116	109,5	105,7	115,7	107,3	106	113,8	101,4	125,1	137																									
Exhaust noise 4)	118,7	119,6	121,7	121,1	122,6	127,4	126,3	137,6	123,6	124,8	122,4	122,3	124	123,6	123,2	122,8	121,7	120,4	120	120	118,6	118,6	118	117,2	116,9	115,8	115,7	115	113,6	132,3	15,5 ⁵⁾																									
3) DIN EN ISO 3746 (σ _{ref} =±4 dB)																	4) Measured in exhaust pipe (f ≤ 250Hz: ±5dB; f > 250Hz: ±3dB)										L _W : Sound power level										S: Area of measurement surface (S _{ref} =1m ²)										5) DIN 45635-11, Appendix A									